




AR2 ORO COB


Factory Assembled Fixture

A low-profile patented fixture with wire management for flush applications and ultra warm dim performance.

<https://qrco.de/bgb22r>



Dimensions



General Specifications

Voltage	24VDC
CRI	97+
Environment	Indoor / Damp Location
Certification	UL Listed 2108
Warranty	12 Year Limited
Dimmable	Yes
TM-21 (LM-80)	>50,000
Ambient Temperature	-4 ~ +122°F (-20 ~ +50°C)
Operating Temperature	-4 ~ +176°F (-20 ~ +80°C)
LED Chips	74/ft.

AR2 Features

<https://qrco.de/bfWcOL>

- Optimized for long runs and tight spaces
- Precise flush mounting with concealed clips and wire raceway
- Architectural-grade polycarbonate lens

ORO™ COB Features

<https://qrco.de/bgb1TL>

- Dot-free illumination
- Smooth dimming performance housed in a discreet, small form
- Consistent, high-fidelity lighting
- Maximum illumination up to 600 Lm/ft.

SKU Builder

1 Brand	2 Voltage	3 Channel	4 Finish	5 Environment	6 Light Engine	7 Output
LCI	24	AR2		D	ORO-COB	
	24 (24VDC)	AR2 (AR2)	*blank* (Aluminum) WH (White) BL (Black)	D (Dry / Damp Location / IP20)	ORO-COB (ORO COB Light Engine)	100 (~100 Lm/ft.) 250 (~250 Lm/ft.) 400 (~400 Lm/ft.) 600 (~600 Lm/ft.)

8 CCT	9 Lens	10 Fixture Length	11 Exact/Optional	12 Side A Wire Length	13 Side A Wire Color & Type	14 Side A Entry
24 (2400K)	TFR (Arch. Frosted)	_I (Inches: 6-96 in.)	E (Exact)	36I (36 in. - Default)	AW (White CL2 - Default)	A (End)
27 (2700K)	TCL (Arch. Clear)	_F (Feet: 0.5-8 ft.)	O (Optional)	_in.	AB (Black CL2)	C (Bottom)
30 (3000K)	AFS (Arch. Frosted Satin Lens)				AS* (Silver Plenum - *Bare Lead only)	
35 (3500K)						

15 Side A Wire Connection	16 Side B Wire Length	17 Side B Wire Color & Type	18 Side B Entry	19 Side B Wire Connection	20 Mounting
					UC
1 (Bare Wire - Default)	*blank* (No Wire - Default)	*blank* (No Wire - Default)	A (End)	1 (Bare Wire - Default)	UC (U-Clip)
2 (Barrel - Female)	_in.	BW (White CL2)	C (Bottom)	2 (Barrel - Male)	
3 (Interconnect - Female)		BB (Black CL2) BS* (Silver Plenum - *Bare Lead only)		3 (Interconnect - Male)	



AR2 ORO COB

Factory Assembled Fixture

A low-profile patented fixture with wire management for flush applications and ultra warm dim performance.

<https://qrco.de/bgb22r>



1 LCI Brand

LCI Lucetta CI


www.LucettaCI.com

2 24 Voltage

24 (24VDC)

3 AR2 Channel

AR2 (AR2)



4 Finish

- *blank* (Aluminum)
- WH (White)
- BL (Black)

5 D Environment

D (Dry / Damp Location / IP20)

6 ORO-COB Light Engine

ORO-COB (ORO COB Light Engine)

7 Output

	100	250	400	600
--	-----	-----	-----	-----

Wattage	1.1 W/ft.	2.7 W/ft.	4.3 W/ft.	6.6 W/ft.
Max Continuous Run (ft.)	50 ft.	35 ft.	22 ft.	14.5 ft.

8 CCT

Lumen Series	100	250	400	600
24 2400K	97 Lm/ft.	246 Lm/ft.	345 Lm/ft.	576 Lm/ft.
27 2700K	99 Lm/ft.	252 Lm/ft.	375 Lm/ft.	580 Lm/ft.
30 3000K	86 Lm/ft.	239 Lm/ft.	384 Lm/ft.	582 Lm/ft.
35 3500K	95 Lm/ft.	245 Lm/ft.	381 Lm/ft.	588 Lm/ft.


9 Lens

TFR (Architectural Frosted Lens)	30% Light Loss	Dotless	
TCL (Architectural Clear Lens)	10% Light Loss	Semi-Diffused	
AFS (Architectural Frosted Satin Lens)	45% Light Loss	Dotless	

10 Fixture Length

- I (Inches: 6-96 in.)
- F (Feet: 0.5-8 ft.)

11 Exact/Optimal





AR2 ORO COB

Factory Assembled Fixture

A low-profile patented fixture with wire management for flush applications and ultra warm dim performance.

<https://qrco.de/bgb22r>



12 Side A Wire Length

36I (36 in. - Default)

in.

13 Side A Wire Color & Type

AW (White CL2 - Default)

AB (Black CL2)

AS* (Silver Plenum - *Bare Lead only)

14 Side A Entry

A (End)

C (Bottom)



15 Side A Wire Connection

Default Wire Gauge: 20/2 AWG*

Contact your Lucetta CI Representative for additional wire gauge options.

1 (Bare Wire - Default) 3.95mm (Dia.)



2 (Barrel - Female) 11.43mm (Dia.)



3 (Interconnect - Female) 6.9mm x 5.6mm (W x H)



16 Side B Wire Length

blank (No Wire - Default)

in.

17 Side B Wire Color & Type

blank (No Wire - Default)

BW (White CL2)


BB (Black CL2)

BS* (Silver Plenum - *Bare Lead only)

18 Side B Entry

A (End)

C (Bottom)



19 Side B Wire Connection

Default Wire Gauge: 20/2 AWG*

Contact your Lucetta CI Representative for additional wire gauge options.

1 (Bare Wire - Default) 3.95mm (Dia.)



2 (Barrel - Female) 11.43mm (Dia.)




3 (Interconnect - Female) 6.9mm x 5.6mm (W x H)



14 UC Mounting

UC (U-Clip)



Total Dimensions (Including Fixture)

U-Clip:
0.56 x 0.64 in. (H x W)



AR2 ORO COB

Factory Assembled Fixture

A low-profile patented fixture with wire management for flush applications and ultra warm dim performance.

<https://qrco.de/bgb22r>




Recommended Power Supplies (Sold Separately)

BIANCO™ U Dimmable Driver

High-performance LED driver with smooth dimming, stable output, and universal compatibility with popular controls and systems.

- Universal dimming support (ELV, Triac, and 0–10V)
- No minimum load
- 100–277VAC universal input
- 0.1% Performance dimming



For more information, visit us at:


<https://qrco.de/bfWcPI>

SKU	General Specs	Input Voltage / Frequency	Output Voltage & Maximum Load	Minimum Load
LCI-BNCU-24V30W-J	Class 2, Dimmable 6.5 x 3.7 x 1.57 in.	100–277VAC, 50/60Hz	24V / 30W	None
LCI-BNCU-24V60W-J	Class 2, Dimmable 7.4 x 3.7 x 1.57 in.	100–277VAC, 50/60Hz	24V / 60W	None
LCI-BNCU-24V96W-J	Class 2, Dimmable 8.66 x 3.7 x 1.57 in.	100–277VAC, 50/60Hz	24V / 96W	None
LCI-BNCU-24V200W-J	Dimmable 10.24 x 4.13 x 1.77 in.	100–277VAC, 50/60Hz	24V / 200W	None
LCI-BNCU-24V300W-J	Dimmable 10.95 x 4.33 x 1.92 in.	100–277VAC, 50/60Hz	24V / 300W	None

VLM Series Constant Voltage Driver

Compact constant-voltage LED driver best utilized in dynamic applications.

- Compatible with PWM low voltage dimming systems
- Provides power for DMX integrated systems
- UL Listed junction box
- Small form factor



For more information, visit us at:

<https://qrco.de/bgZJJs>

SKU	General Specs	Input Voltage / Frequency	Output Voltage & Maximum Load	Minimum Load
LCI-VLM-24V60W-J	Class 2 8.19 x 2.94 x 1.31 in.	120 / 277VAC, 47 - 63Hz	24V / 60W	None
LCI-VLM-24V100W-J	Class 2 8.19 x 2.94 x 1.31 in.	120 / 277VAC, 47 - 63Hz	24V / 96W	None



AR2 ORO COB

Factory Assembled Fixture

A low-profile patented fixture with wire management for flush applications and ultra warm dim performance.

<https://qrco.de/bgb22r>



Safety

UL Listed 2108 Low Voltage Luminaires. Certified for United States and Canada. File # E506975.

Approved for storage areas of clothes closets per NEC 410.16.A.3 and 410.16.C.5

Performance

Can be used to comply with TITLE 24 Part 6 High Efficacy Lighting LED requirements - JA8-2016-2022-E

LED chip data measured in accordance to IES LM-80-08.

Photometric & Colorimetry data measured in accordance to IES LM-79-08, in Elemental LED's Innovation Lab.

Safety / Warnings / Disclosures

Install in accordance with national and local electrical code regulations.

This product is intended to be installed and serviced by a qualified, licensed electrician.

Only use copper wiring. Use wires rated for at least 176°F (80°C) and certified for use with external connection of electrical equipment.

Tape light, attached wire leads, and additional extension cables, connectors, etc., are not rated for in-wall installation unless otherwise noted. Tape light and attached wire leads are field-cuttable.

Ensure applicable wire is installed between driver, fixture, and any controls in-between. When choosing wire, factor in voltage drop, amperage rating, and type (in-wall rated, wet location rated, etc.). Inadequate wire installation could overheat wires, and cause fire.

Do not install in environment where LED chips are exposed to direct sunlight as damage to the phosphor will occur.

Do not install in environment where excessive heat may exist (ex. close proximity to fireplace, etc.) See Ambient Temperature ratings

Do not modify product beyond instructions or warranty will be void.

Actual color may vary from what is pictured on this sheet and other print materials due to the limitations of photographic processes.

We reserve the right to modify and improve the design of our fixtures without prior notice. We cannot guarantee to match existing installed fixtures for subsequent orders or replacements in regards to product appearance, CCT, or lumen output.

Warranty

12 Year Limited

This warranty does not include the additional accessories referenced in this specification sheet. Complete warranty details for fixtures and additional accessories are available at www.dioleed.com/limited-warranty/ within the Policies section. For warranty related questions please contact product support.

Elemental LED, Inc. stands behind its products when they are used properly and according to our specifications. By purchasing our products, the purchaser agrees and acknowledges that lighting design, configuration and installation is a complex process, wherein seemingly minor factors or changes in layout and infield adjustments can have a significant impact on an entire system. Choosing the correct components is essential. Elemental LED is able to work with the original purchaser to make an appropriate product selection to the extent of the limited information that the customer can provide, but it is virtually impossible for Elemental LED to design a system that foresees every unknown factor. For this reason, this Warranty does not cover problems caused by improper design, configuration or installation issues. Any statement from a Elemental LED employee or agent regarding a customer's bill of goods and/or purchase order is NOT an acknowledgment that the products purchased are designed and configured correctly. The purchase agrees and acknowledges that it is the customer's responsibility to adhere strictly to all information contained in the Product Specification Sheets.

There is often more than one way to design, configure and layout an LED lighting application properly to achieve the same lighting effect. Elemental LED strongly recommends that licensed professionals be used in the design and installation of lighting systems that include Elemental LED products. The specifications include important information that a designer and installer should carefully review and strictly follow. Qualified designers and certified and/or licensed installers, with access to the final installation environment, customer goals, and Elemental LED product specifications can make the requisite decisions appropriate for a successful finished lighting application.

- Lumen value measured in accordance to IES LM-79-08. LED chips have a luminous flux range with a tolerance of +/- 5%.
- Each maximum run requires a dedicated power feed from the driver. Do not extend beyond the recommended maximum run length. Max run may exceed Class 2 limit. Actual wattage may differ from calculated wattage due to voltage drop across run.
- Do not install product in an environment outside the listed ambient temperature. Exceeding the maximum ambient temperature may damage LED chips, reduce the total lamp life, lumen output, and/or adversely impact color consistency.
- Actual efficacy value is dependent to specified LED driver (power supply). An estimated efficacy value can be calculated as follows: Lumen value divided by average power consumption per foot.
- Operating temperature is measured according to the minimum and maximum ambient temperature environment.